§ 800.83

the original inspection service was performed and that the quality or condition of the grain in the samples has not changed.

(2) Certificate statement. When the results of a reinspection, appeal inspection, or Board appeal inspection service are based on an official file sample, the certificate for the reinspection service, the appeal inspection service, and the Board appeal inspection service shall show a statement, as specified in the instructions, indicating that the results are based on the official file sample.

[50 FR 49670, Dec. 4, 1985]

§800.83 Sampling provisions by kind of movement.

(a) Export cargo movements—(1) Bulk grain. Except as may be approved by the Administrator on a shipment-byshipment basis in an emergency, each inspection for official grade, official factor, or official criteria on an export cargo shipment of bulk grain shall be performed on official samples obtained from the grain (i) as the grain is being loaded aboard the final carrier; (ii) after the final elevation of the grain prior to loading and as near to the final loading spout as is physically practicable (except as approved by the Administrator when representative samples can be obtained before the grain reaches the final loading spout); and (iii) by means of a diverter-type mechanical sampler approved by the Service and operated in accordance with instructions. If an approved diverter-type mechanical sampler is not properly installed at an elevator or facility as required, each certificate issued at that elevator or facility for an export cargo shipment of bulk grain shall show a statement indicating the type of approved sampling method used, as prescribed in the instructions.

(2) Sacked grain. Each inspection for official grade, official factor, or official criteria on an export cargo shipment of sacked grain shall be performed on official samples obtained from the grain by any sampling method approved by the Service and operated in accordance with instructions.

(b) Other movements. Each inspection for official grade, official factor, or official criteria on a domestic cargo

movement ("In," "Out," or en route barge movement), a movement in a land carrier (any movement in a rail-car, truck trailer, truck/trailer combination, or container), or a "LOCAL" movement of bulk or sacked grain shall be performed on official samples obtained from the grain by any sampling method approved by the Service and operated in accordance with the instructions.

[50 FR 49670, Dec. 4, 1985]

§ 800.84 Inspection of grain in land carriers, containers, and barges in single lots.

(a) General. The inspection of bulk or sacked grain loaded or unloaded from any carrier or container, except shiplot grain, must be conducted in accordance with the provision in this section and procedures prescribed in the instructions. Applicant must provide written instructions to official personnel, reflecting contract requirements for quality and quantity for the inspection of multiple carriers graded on a composite grade or average grade basis.

(b) Single and multiple grade procedure—(1) Single grade. When grain in a carrier(s) is/are offered for inspection as one lot and the grain is found to be uniform in condition, the grain must be sampled, inspected, graded, and certified as one lot. For the purpose of this paragraph, condition only includes the factors heating and odor.

(i) Composite grade. Grain loaded in multiple carriers offered for inspection may be combined into a single sample for grade analysis and certified as a single lot, provided that the grain in each individual carrier is inspected and found uniform in respect to odor, condition, and insect infestation, and sampling is performed at the individual loading location in a reasonably continuous operation. The maximum number of individual units that may be combined to form a composite grade analysis is 20 containers, 5 railcars, or 15 trucks. Composite analysis must be restricted to carriers inspected within the official service provider's area of responsibility.

(ii) Average grade. Grain loaded in multiple carriers offered for inspection may be graded individually, then averaged for certification as a single lot,